

**THIS PAGE IS INSERTED BY OIPE SCANNING
AND IS NOT PART OF THE OFFICIAL RECORD**

Best Available Images

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

BLACK BORDERS

TEXT CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT

BLURRY OR ILLEGIBLE TEXT

SKEWED/SLANTED IMAGES

COLORED PHOTOS HAVE BEEN RENDERED INTO BLACK AND WHITE

VERY DARK BLACK AND WHITE PHOTOS

UNDECIPHERABLE GRAY SCALE DOCUMENTS

**IMAGES ARE THE BEST AVAILABLE
COPY. AS RESCANNING *WILL NOT*
CORRECT IMAGES, PLEASE DO NOT
REPORT THE IMAGES TO THE
PROBLEM IMAGE BOX.**

ANTIBACTERIAL BUILDING MATERIAL

Patent number: JP11236734
Publication date: 1999-08-31
Inventor: MIYAZAKI NORIHIKO
Applicant: KAWAI MUSICAL INSTR MFG CO LTD
Classification:
- international: E04B1/62; C09D5/14
- european:
Application number: JP19980038897 19980220
Priority number(s):

Abstract of JP11236734

PROBLEM TO BE SOLVED: To provide an antibacterial building material having excellent workability in a painting process and having uniform superior antibacterial properties extending over the whole surface.

SOLUTION: The antibacterial building material is used as a building material for interior finishing such as a floor material, a wall material, a ceiling material, etc., and the surface of the antibacterial building material is coated with an antibacterial ultraviolet curing type coating composition, to which 0.1-20 wt.% amino acid salt of an antibacterial metal at a weight ratio to the solid content of an ultraviolet curing type coating composition is added and mixed while using the ultraviolet curing type coating composition mainly comprising an ultraviolet cured resin as a base. Since the coating composition has viscosity lower than conventional antibacterial paints, workability in a painting process is improved and the dispersing quality of an antibacterial component is enhanced, the surface of the building material has uniform excellent antibacterial properties extending over the whole surface. Since the loading of amino acid salt is prepared in 0.1-20 wt.%, the color of the surface is not changed by ultraviolet rays.